




YOUR HOSE FOR EDIBLE OILS

A Flexible suction and discharge hose for filling and discharging animal and vegetable oils and fats.



SPECIFICATIONS

I.D (mm)	O.D (mm)	WALL THICKNESS (mm)	WORKING PRESSURE (bar)	NUMBER OF INSERTS	MIN. BEND RADIUS (mm)	WEIGHT APPROX. KG/M	ROLL LENGTH
25	37	6	10	2	85	1	40
32	44	6	10	2	105	1.25	40
38	51	6.5	10	2	120	1.45	40
40	54	7	10	2	140	1.7	40
50	64	7	10	2	160	2	40
50	61	5.5	10	2	160	1.75	40
50.8	62	5.5	10	2	160	1.8	40
53	64	5.5	10	2	170	1.9	40
63.5	76.5	6.5	10	2	210	2.35	40
65	79	7	10	2	210	2.55	40
75	90	7.5	10	2	250	3.2	40
76.2	90.2	7	10	2	250	3.3	40
80	96	8	10	2	260	3.65	40
102	122	10	10	4	330	5.5	40

Application: Flexible suction and discharge hose with plastic helix, for filling and discharging animal and vegetable oils and fats as well as other fatty goods. Also suitable for the food and drinks industry conveying milk and dairy products.

STANDARDS AND APPROVALS

BfR (former Bg VV) XXI:2002 (Kat.2), FDA (CFR 21 177.2600)

TEMPERATURE RANGE

-35 C / + 80 C Steam Cleaning up to max. 130 C / 30min unpressurised.

SAFETY FACTOR

3.15:1

TUBE

NBR, White, smooth, food quality, grease and oil resistant.

REINFORCEMENT

Textile Wrapped, plastic helix.

COVER

NVC, Blue, resistant to abrasion and ageing, cloth impression.

MARKINGS

White transfer tape.