


OIL MASTER SD PETROL/OIL SUCTION & DELIVERY







APPLICATION Hardwall hose used for the suction and delivery of unleaded gasoline and fuels with aromatic content of up to 50%. Suitable for use on tanker trucks.

MATERIAL
Inner Tube – Smooth NBR1 antistatic rubber.
Cover – Smooth wrapped finish, antistatic, synthetic rubber, weathering, abrasion ozone and oil resistant.
Reinforcement – High strength synthetic cord with steel helix wire.
Electrical Resistance – OHM/T Electrically conductive hose, $R < 1 \times 10^6$ OHM/lgh for lengths equal or lower than 40m. The hose can be used in atex areas.

COLOUR Black

TEMPERATURE – 30°C to +125°C
 Minimum operating temperature –40°C



PART NO.						
	I.D	O.D	REEL	W.P	B.P	VACUUM
	MM	MM	LENGTH (M)	BAR	BAR	BAR
OILP-SD-19-120	19	32	120	16	64	0.9
OILP-SD-25-120	25	38	120	16	64	0.9
OILP-SD-32-120	32	45	120	16	64	0.9
OILP-SD-38-120	38	52	120	16	64	0.9
OILP-SD-50-120	50	65.5	120	16	64	0.9
OILP-SD-63-120	63.5	78.5	120	16	64	0.9
OILP-SD-75-120	75	90	120	16	64	0.9
OILP-SD-100-120	100	116	120	16	64	0.9

SAFETY FACTOR 4:1